



PRIMER S

SCHEDA TECNICA

Rev. 0 – Ed. 1

SPECIFICATIONS

PRIMER S is white and can be coloured if necessary, it gives a slightly "rough"-effect primer specifically employed to facilitate the adhesion of decorative finishes such as (STUCCOMARMO, DECORA'etc) particularly smooth supports with a low absorption degree (such as concrete, cellular cement, plasterboard, plaster).

COMPOSITION

Acrylic emulsion, special surface-active agents, quartz grains, other additives

METHODS OF APPLICATION

Apply directly with a paint brush or roller, dilute with 20-40% of water

DATI TECNICI

SPECIFIC WEIGHT:	1,682 Kg./Lt. +/- 0,5%
VISCOSITY	thixotropic
COLOUR:	white
YIELD :	7-8 m ² /Lt.
DILUIZIONE:	20 - 40% with water
PACKEGING:	Lt, 15, Lt. 4 , Lt.0,750 polyethylene containers
DRYING:	30 minutes to the touch – completely dry in 24 hours at 20°C
OVERPAINTING DEGREE	24h
APPLICATION	brush or roller
PRESERVATION:	36 months in the intact packages, away from temperature changes

ITEM OF SPECIFICATIONS

Pre-treatment of crumbly wall surfaces with one coat of highly-adherent rough primer like PRIMER S produced by Spiver Ltd.
Price inclusive of the material and implementation, except the scaffoldings per square metre: €.....

NB The above-mentioned data are susceptible of variations. Spiver Ltd. Is not responsible for any negative result depending on the application of the product out of the company's control and on the agents unrelated to the product quality.