

	<h1>PRIMER RV</h1>	<p style="text-align: center;">SPECIFICATIONS</p> <hr/> <p>Rev. 0 – Ed. 1</p>
---	--------------------	--

SPECIFICATIONS AND FIELDS OF EMPLOYMENT

PRIMER RV is a “rough”-effect primer specifically employed to facilitate the adhesion of plasters on particularly smooth supports with a low absorption degree (such as concrete, cellular cement, plasterboard, plaster).

It is in fact applied as a binding element on those difficult supports where common plasters do not easily adhere, such as:

- marmorino or lime-based plasters on plasterboard, plaster or cellular cement;
- ceramic tiles.

COMPOSITION

Acrylic emulsion, special surface-active agents, quartz grains, other additives.

METHODS OF APPLICATION

Dilute the product with 50% of water and apply with a paintbrush or roller. Stir the compound at regular intervals.

TECHNICAL DATA

SPECIFIC WEIGHT:	1,239 kg/Lt. +/- 0,5%
VISCOSITY:	thixotropic
YIELD:	7 – 8 m ² /lt.
DILUTION:	50% with water
PACKAGE:	15 – 4 – 0,750-lt. polyethylene cases available
DRYING:	30 minutes to the touch – completely dry in 24 hours at 20°C
OVERPAINTING DEGREE:	24 hours
APPLICATION:	paintbrush, roller
PRESERVATION:	36 months in the intact packages, away from temperature changes

ITEM OF SPECIFICATIONS

Pretreatment of crumbly wall surfaces with one coat of highly-adherent rough primer like PRIMER RV produced by Spiver Ltd. Price inclusive of the material and implementation, except the scaffoldings per square metre: €.....

NB The above-mentioned data are susceptible of variations. Spiver Ltd. is not responsible for any negative result depending on the application of the product out of the Company’s control and on the agents unrelated to the product quality.